SNAPPER.



2016 Lawn Tractors & Zero Turns

The Easy Choice.



Rear Engine RidersPage 6



SPX™ Lawn Tractors Page 8



Zero Turn Mowers Page 10



Attachments
Page 18

Easy to Use. Easy to Own.

Snapper® Riding Mowers take practical, innovative features and integrate them into a straightforward design that's easy-to-use and easy-to-own. It's that simple.

Top 4 Reasons to Choose a Snapper® Dealer



1. Snapper® Dealers are Mower Experts
You can actually talk to someone who really
knows what they're talking about. Friendly,
straight talk you can't get anywhere else.



2. Try it Out

Test drive your new mower to learn how to operate it.



3. Hassle-Free Purchase
Your Snapper® Dealer can get you started with
your new mower including set-up and delivery.



4. Service Support When You Need it Factory-trained service technicians and a stocked parts department will keep you mowing for years to come.

2 | SNAPPER.COM | SNAPPER.COM



Sit back, relax and enjoy the ride. Snapper® Riding Mowers continue the tradition of making yard work easy with a variety of models - all including a streamlined modern design, versatile cutting options and simple-to-use features.







Rider in action.



Rear Engine Riders



Some dependable designs are

power a moveable rubber disc.

HI VAC® Mower Deck

Similar to a vacuum, the HI VAC® Mower ingeniously simple. Snapper's disc drive Deck efficiently cuts and vacuums up transmission uses a spinning plate to grass clippings for a clean finish. The secret to the cut is the unique blade and rolled deck edge that generates a large volume of air and creates suction.



Optional NINJA® Mulching Blade

Finely mulch your grass with our exclusive NINJA® Blade that features six powerful cutting surfaces. While the blade mulches the grass clippings, the deck design blows them back into the



Briggs & Stratton® Engines offer the reliability you can count on when mowing the lawn.



Easy-to-Use Design

After 50 years, the rear engine rider has been reinvented to combine tried and true features with today's latest innovations. An easy-to-use design with enhanced features still delivers the same dependability you would expect from a mowing icon.



User-Friendly Controls

Fingertip controls make the rear engine rider simple to drive.

RE110 28" Deck 11.5 Gross HP*	RE130 33" Deck 13.5 Gross HP*	RE210 33" Deck 15.5 Gross HP*		
344cc Briggs & Stratton PowerBuilt™ Engine	500cc Briggs & Stratton PowerBuilt™ Engine	500cc Briggs & Stratton Professional Series™ Engine		
HI VAC® Mower Deck	HI VAC® Mower Deck	HI VAC® Mower Deck		
Disc Drive Transmission	Disc Drive Transmission	Hydrostatic Transmission		
3-Year Limited Warranty [†]	3-Year Limited Warranty [†]	3-Year Limited Warranty [†]		

*All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton. †See operator's manual or dealer for complete warranty details. For a full list of specifications, please see page 20. Attachment listing, please see page 18.

See What Snapper® Owners are Saying:

 $\star\star\star\star\star$ 5 out of 5 stars

Small footprint in my garage, GREAT job on my lawn!

"LOVE the handling, speed range (especially with new notched shift plate they provided free), easy change from side chute to mulch, and small storage space needed in my garage. Best rider I've owned for my 1/3 acre yard." -Snapper John

To read more customer reviews like this visit www.snapper.com

An American Classic Reborn.





SPX[™] Series



Step Up to High Value

All-steel construction including the hood, cast-iron front axle and a hydrostatic transmission are hallmarks of premium tractors all at a value price.



Quick-Adjust Cutting Height

Easy-to-use height-of-cut controls adjust the mower deck for changing grass conditions.



Fabricated Mower Decks

The durable 42" and 48" fabricated mower decks feature welded, heavyduty steel for non-stop mowing season-after-season. All fabricated decks come with a limited lifetime warranty*.



Step On It

Our responsive foot pedals give you hands-free control over forward and reverse speed. The dash-mounted cruise control lets you set your speed.



Turning Perfection

With a 14" turning radius, you can spend less time mowing and more time enjoying your yard.



A Generation of Power

Briggs & Stratton Professional Series"
V-Twin OHV Engines have full-pressure
lubrication and spin-on oil filters for
years of trouble-free performance.

SPX™ 22/4242" Deck
33 Grees HB*

724cc Briggs & Stratton Intek™ V-Twin Engine

Hydro-Gear® T2-HP™ Hydrostatic

3-Year Limited Warranty[†]

SPX[™] 22/46 46" Deck

724cc Briggs & Stratton Professional Series™ V-Twin Engine

Hydro-Gear® T2-HP™ Hydrostatic

3-Year Limited Warranty[†]

SPX[™] 23/42 42" Fabricated Deck 23 Gross HP*

724cc Briggs & Stratton Professional Series™ V-Twin Engine

Hydro-Gear® T2-HP™ Hydrostatic

Fabricated Deck - Limited Lifetime Warranty[†]

3-Year Limited Warranty[†]

SPX[™] 25/48 48" Fabricated Deck 25 Gross HP

724cc Briggs & Stratton Professional Series™ V-Twin Engine

Hydro-Gear® T2-HP™ Hydrostatic

Fabricated Deck - Limited Lifetime Warranty[†] 3-Year Limited Warranty[†]

*All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.
†See operator's manual or dealer for complete warranty details. For a full list of specifications, please see page 21.

Attachment listing, please see page 18.

See What Snapper® Owners are Saying:

★★★★★ 5 out of 5 stars **Great Ride**

"The performance is simply awesome. This is a very well thought out machine. Turn radius is as advertised, plus the mower is comfortable to operate." - Glennj

To read more customer reviews like this visit www.snapper.com

Straightforward Design.







atch the 360Z

Data rates apply.

360Z



Commercially-Inspired

A fully-welded steel frame, thick-walled front axle, durable mower deck, and ball bearings in the caster spindles ensure durability and a



High performance engine options include Briggs & Stratton Intek™, Briggs & Stratton Professional Series[™] with ReadyStart[®], and the Kawasaki® FR651V, making sure your zero turn mower has the power to perform year after year.



Heavy-Duty Mower Decks

A durable stamped or fabricated steel mower deck provides non-stop mowing season after season. All fabricated decks come with a limited lifetime



More Than Just a Zero Turn

Snapper's first dirt-hauling, tool-toting, flower-delivering and, of course, grass-cutting zero turn mower. The integrated cargo bed* provides on-the-go versatility and convenience. Plus, the rail system is compatible with numerous third-party UTV/ATV accessories for added utility around your yard.



The Choice is Yours

The commercial-style foot-operated mower deck lift easily lifts and adjusts the mower deck between 13 height-of-cut positions from 1.5 to 4.5 inches.

360Z 22/46 46" Deck 22 Gross HP*

724cc Briggs & Stratton Intek™V-Twin Engine Hydro-Gear® EZT® Hydrostatic Transaxles Optional Cargo Bed[‡]

3-Year Limited Warranty[†]

360Z 23/42 42" Deck 23 Gross HP*

724cc Briggs & Stratton Professional Series™ V-Twin Engine with ReadyStart® Hydro-Gear® EZT® Hydrostatic Transaxles

Optional Cargo Bed[‡] Fabricated Deck - Limited Lifetime Warranty

3-Year Limited Warranty[†]

360Z 23/48 48" Deck 23 Gross HP

724cc Briggs & Stratton Professional Series[™] V-Twin Engine with ReadyStart®

Hydro-Gear® EZT® Hydrostatic Transaxles

Cargo Bed‡ Fabricated Deck - Limited

Lifetime Warranty 3-Year Limited Warranty

360Z 21.5/48 48" Deck 21.5 Gross HP** 360Z 25/52 52" Deck 25 Gross HP*

726cc Kawasaki[®] FR Series V-Twin Engine

Hydro-Gear® EZT® Hydrostatic Transaxles

Fabricated Deck - Limited

3-Year Limited Warranty[†]

Lifetime Warranty

Cargo Bed‡

724cc Briggs & Stratton Professional Series™ V-Twin Engine with ReadyStart®

Hydro-Gear® ZT-2800® Hydrostatic Transaxles

Cargo Bed[‡]

Fabricated Deck - Limited Lifetime Warranty[†]

3-Year Limited Warranty[†]

*All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton





New Levels of Versatility.





Watch the 400Z in action. Data rates apply.

400Z



More Choices

More is better when it comes to cutting height options with 12 different settings from 1.5 to 4.5 inches high. The foot-pedal assisted deck lift makes changing mowing heights easier.



Mow More. Stop Less

Its wide-neck 5.5 gallon fuel tank and easy-off cap holds more fuel for your uninterrupted mowing pleasure.



Engine Protection

This wrap-around steel engine enclosure helps protect critical components.



Turf-Friendly

There's a fine line between turf traction and turf damage. That's why the large, turf-friendly tires leave grass just like you found it, but shorter.



Rugged Durability

With its heavy-duty, all-steel construction frame, contour hugging front axle and reliable Hydro-Gear® Transaxles, this zero turn is built to perform year after year.



Workhorse

Built for harsh zero turn mowing conditions, the Briggs & Stratton® Commercial Series Engine has what it takes to perform, including an advanced debris management system and beefed up cylinder block.

400Z 21.5/48 48" Fabricated Deck 21.5 Gross HP*

726cc Kawasaki® FR Series V-Twin Engine Hydro-Gear® ZT-2800® Hydrostatic Transaxles Fabricated Deck - Limited Lifetime Warranty[†] 3-Year Limited Warranty[†] 400Z 25/48 48" Fabricated Deck 25 Gross HP"

724cc Briggs & Stratton® Commercial Series V-Twin Engine
Hydro-Gear® ZT-2800® Hydrostatic Transaxles
Fabricated Deck - Limited Lifetime Warranty†

3-Year Limited Warranty†

*All power levels are provided by Kawasaki.

**All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

†See operator's manual or dealer for complete warranty details.

For a full list of specifications, please see page 23.

Attachment listing, please see page 19.

See What Snapper® Owners are Saying:

★★★★★ 5 out of 5 stars **BEST EVER**

"The best money I ever spent. I can't keep my son-in-law off my mower." - GW1956

To read more customer reviews like this visit www.snapper.com

The Right Mower for the Big Job.





550Z



Durable Hydro-Gear® Transaxles

Built for high-performance applications, the Hydro-Gear® ZT-3100® Hydrostatic Transaxles deliver smooth control while changing directions and speeds.



Wide, 52" or 61" fabricated mower decks made from thick 10-gauge steel mow grass in no time with speeds up to 8 mph. Welded and reinforced for years of repeat mowing and are also backed by a limited lifetime warranty



Simple Height-of-Cut

Convenient foot-assisted deck lift easily adjusts cut-height from 1.5 to



Easy to Service

Direct access to the top of the deck for service-friendly maintenance.



Commercial Series Engine

Built for harsh zero turn mowing conditions, the Briggs & Stratton® Commercial Series Engine has what it takes to perform, including an advanced debris management system and beefed up cylinder block.



Kawasaki® FR Series Engine

Built for power, the Kawasaki® FR Series Engine offers smooth power output and outstanding durability in a compact design.



Intuitive Controls

Easy-to-use controls are all conveniently located within reach.

550Z 24/52 52" Fabricated Deck 24 Gross HP**

726cc Kawasaki® FR Series V-Twin Engine

Hydro-Gear® ZT-3100® **Hydrostatic Transaxles** Fabricated Deck - Limited

Lifetime Warranty[†]

3-Year Limited Warranty[†]

550Z 25/52 52" Fabricated Deck

25 Gross HP*

3-Year Limited Warranty[†]

724cc Briggs & Stratton® Commercial Series V-Twin Engine

Hydro-Gear® ZT-3100® Hydrostatic Transaxles

Fabricated Deck - Limited Lifetime

550Z 24/61 61" Fabricated Deck 24 Gross HP*

726cc Kawasaki® FR Series V-Twin Engine

Hydro-Gear® ZT-3100® **Hydrostatic Transaxles** Fabricated Deck - Limited

Lifetime Warranty[†] 3-Year Limited Warranty[†]

550Z 25/61 61" Fabricated Deck 25 Gross HP*

724cc Briggs & Stratton® Commercial Series V-Twin Engine

Hydro-Gear® ZT-3100® Hydrostatic Transaxles Fabricated Deck - Limited Lifetime

Warranty[†]

3-Year Limited Warranty[†]

*All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton. **All power levels are provided by Kawasaki. †See operator's manual or dealer for complete warranty details. For a full list of specifications, please see page 23. Attachment listing, please see page 19. **See What Snapper® Owners are Saying:**

★★★★★ 5 out of 5 stars

Great mower

"Very pleased with this mower. It mows smoothly, has plenty of power, and is well constructed. I am in the process of purchasing a second one, it works that well." -Fireguy1

To read more customer reviews like this visit www.snapper.com

Professional Grade.



It's Easy to Get Attached.

When it comes to lawn care, regular mowing is not always good enough. Sometimes you want a variety of tools at your fingertips to complete the broad range of tasks for a great looking lawn.

Featured Tractor Attachments



42" DOZER BLADE

Adjustable to fit the right angle or position, dozer blades are spring-loaded to absorb shock and make it easy to handle snow removal and yard chores.



GRASS MULCHER KIT

Reduce your number of clippings by finely mulching them back into the lawn. NINJA® mulching blade available for Rear Engine Rider



36" TOW-REHIND TILLER

Easily prepare your soil for spring with the 36" tow-behind tiller.



40" TOW-REHIND DETHATCHER

Easily remove thatch for your lawn by pulling a dethatcher from behind your tractor.



SINGLE BAG COLLECTOR

Also available as a double bag collector, the removable bag(s) collect grass clippings. Fits Rear Engine Rider



CLEAN SWEEP™ TWIN COLLECTOR Roomy enough for 6.5-bushels of clippings in

two easy-to-empty bags. Fits Rear Engine Rider, SPX™ (42"), 360Z



TURBO CLEAN SWEEP™ TRIPLE COLLECTOR Roomy enough for 10-bushels of clippings in

three easy-to-empty bags.



TURBO BLOWER

Easily attaches to the mower and gets power directly from the engine. The blower pushes clippings and debris into a bagger for a

Fits SPX™ (46", 48"), 360Z (52")



lifting out of yard work. Fits Rear Engine Rider, SPX™



REAR WHEEL WEIGHTS

Multi-functional, 10 cu.ft. cart takes the heavy- These 33-lb. weights attach easily to provide the extra stability needed when working on slippery ground.



Tractor Cover Fits Rear Engine Rider, SPX™ Headlight Kit Fits Rear Engine Rider Front Double Bar Bumper Fits SPX"

> Tire Chains Fits SPX"

NOT SEEING THE ATTACHMENT YOU ARE LOOKING FOR?

CONTACT YOUR LOCAL DEALER FOR MORE INFORMATION AND ASSISTANCE WITH SELECTING THE RIGHT ATTACHMENT FOR YOUR TRACTOR OR ZERO TURN. AS WELL AS INSTALLATION ASSISTANCE.

VISIT SNAPPER.COM TO ENTER YOUR ZIP CODE TO LOCATE YOUR SNAPPER® DEALER.

Featured Tractor Snow Attachments



SOFT-SIDED SNOW CAB

snow cab, complete with clear, shatterproof, non-fogging Lexan® windows. Fits SPX™ (Cab may vary by model.)



42" SINGLE-STAGE SNOWTHROWER

rugged single-stage snowthrower.



REAR CARRIER, WEIGHTS AND CHAINS

Keep the howling, cold wind out with our vinyl Make short work of the deepest snow with this Weight carrier, weights and chains install easily. Weights (33-lbs.) enhance traction with front attachments. Fits SPX"

Featured Zero Turn Mower Attachments



INTEGRATED CARGO BED

Make your zero turn mower more versatile than ever before with an integrated rear cargo bed with a 50-lb. capacity. Fits 360Z (Standard on Most Models)



CARGO BED ACCESSORIES



The integrated rear cargo bed's rail system is compatible with numerous third-party UTV/ATV accessories* for added utility and versatility around your yard. Fits 360Z Cargo Bed



TRAILER HITCH KIT

Turn your zero turn into a towing workhorse with our trailer hitch kit. Fits 400Z, 550Z



GRASS MULCHING KIT

Select kits include dedicated mulching blades, baffles, hardware and instruction sheet. Fits 360Z, 400Z, 550Z



TURBO-PRO™ TWIN CATCHER

Twin catcher collection system holds up to 6-bushels of clippings and is simple to install on zero turn mowers. Fits 400Z



TRIPLE COLLECTOR

Collects up to 10-bushels of clippings into three easy-to-empty grass bags.



Add arm rests to your vinyl seat for additional comfort while mowing your lawn. Fits 360Z, 400Z, 550Z



Fits 360Z, 400Z, 550Z Mesh Seat Kit Fits 360Z

Flat Free Castor Tire Assembly Fits 400Z, 550Z Hour Meter Kit

Fits 360Z - Standard on 400Z, 550Z

Tractor Specifications

Model	RE110	RE130	RE210	SPX™ 22/42	SPX™ 22/46	SPX™ 23/42	SPX™ 25/48
Engine							
Brand	Briggs & Stratton PowerBuilt™ OHV	Briggs & Stratton PowerBuilt™ OHV	Briggs & Stratton Professional Series™ OHV	Briggs & Stratton Intek™ V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV
Gross Horsepower* / Cylinders	11.5 / 1	13.5 / 1	15.5 / 1	22 / 2	22 / 2	23 / 2	25 / 2
Engine Displacement (cc)	344	500	500	724	724	724	724
Choke / Throttle	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic
Start Type	Key	Кеу	Key	Кеу	Key	Key	Key
Engine Features	N/A	N/A	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter
Fuel Tank Capacity (U.S. Gallons)	2	2	2	3.5	3.5	3.5	3.5
12V Battery (cca)	190	190	190	230	230	230	230
Transmission							
Transmission Make	Snapper® Disc Drive	Snapper® Disc Drive	Hydro-Gear® T2®	Hydro-Gear® T2-HP™	Hydro-Gear® T2-HP™	Hydro-Gear® T2-HP™	Hydro-Gear® T2-HP™
Differential	8-Speed, Disc Drive	8-Speed, Disc Drive	Hydro	Hydro	Hydro	Hydro	Hydro
Speed Control Design	Gear Shift Lever	Gear Shift Lever	Foot Pedals	Foot Pedals	Foot Pedals	Foot Pedals	Foot Pedals
Speed- Fwd / Rev. (mph)	1 - 4.5 / 0 - 1.9	1 - 4.5 / 0 - 1.9	0-5/0-2	0 - 5.5 / 0 - 3.3	0 - 5.5 / 0 - 3.3	0 - 5.5 / 0 - 3.3	0 - 5.5 / 0 - 3.3
Brake	Friction	Friction	Disc	Disc	Disc	Disc	Disc
Chassis	<u></u>						
Frame	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel
Front Axle	Welded Steel	Welded Steel	Welded Steel	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron
Turning Radius (inches)	20	20	20	14	14	14	14
Front Tires (inches)	11 x 4	11 x 4	13 x 5	15 x 6	15 x 6	15 x 6	15 x 6
Rear Tires (inches)	16 x 6.50	16 x 6.50	16 x 6.50	20 x 8	20 x 8	20 x 10	20 x 10
Number of Anti-Scalp Wheels	N/A	N/A	N/A	2	4	4	4
Seat	11" Mid-back, Adjustable	11" Mid-back, Adjustable	11" Mid-back, Adjustable	15" Mid-back, Adjustable	15" Mid-back, Adjustable	15" Mid-back, Adjustable	15" Mid-back, Adjustable
Steering	Wheel	Wheel	Wheel	Soft Grip, Wheel	Soft Grip, Wheel	Soft Grip, Wheel	Soft Grip, Wheel
Mower Deck	Wilcet	Wilcet	White	Soft drip, wheet	John Grip, Wheet	Soft drip, wheet	Soft drip, wheet
monor book							
Deck Type	Stamped	Stamped	Stamped	Stamped Steel	Stamped Steel	Fabricated Steel	Fahricated Steel
	Stamped 28	Stamped	Stamped	Stamped Steel	Stamped Steel	Fabricated Steel	Fabricated Steel
Cutting Width (inches)	28	33	33	42	46	42	48
Cutting Width (inches) Mower Configuration	28 HI VAC®	33 HI VAC®	33 HI VAC®	42 Side Discharge	46 Side Discharge	42 Side Discharge	48 Side Discharge
Cutting Width (inches) Mower Configuration Number of Blades	28 HI VAC® 1	33 HI VAC® 1	33 HI VAC® 1	42 Side Discharge 2	46 Side Discharge 3	42 Side Discharge 2	48 Side Discharge 3
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches)	28 HI VAC® 1 1.5 - 4	33 HI VAC® 1 1.5 - 4	33 HI VAC® 1 1.5 - 4	42 Side Discharge 2 1.5 - 4	46 Side Discharge 3 1.5 - 4	42 Side Discharge 2 1.5 - 4	48 Side Discharge
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions	28 HI VAC® 1 1.5 - 4	33 HI VAC® 1 1.5 - 4	33 HI VAC® 1 1.5 - 4	42 Side Discharge 2 1.5 - 4 7	46 Side Discharge 3 1.5 - 4 7	42 Side Discharge 2 1.5 - 4 7	48 Side Discharge 3 1.5 - 4 7
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement	28 HI VAC® 1 1.5 - 4 6 Manual Lever	33 HI VAC® 1 1.5 - 4 6 Manual Lever	33 HI VAC® 1 1.5 - 4 6 Manual Lever	42 Side Discharge 2 1.5 - 4 7 Electric	46 Side Discharge 3 1.5 - 4 7 Electric	42 Side Discharge 2 1.5 - 4 7 Electric	48 Side Discharge 3 1.5 - 4 7 Electric
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No	42 Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor Dimensions	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes Yes No	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes Yes No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor Dimensions Length x Width x Height (inches)	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor Dimensions Length x Width x Height (inches) Limited Warranty'	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 61 x 45	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor Dimensions Length x Width x Height (inches) Limited Warranty' Residential	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No 66 x 32 x 43	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No 66 x 37 x 43	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No No No 66 x 37 x 43	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 55 x 45	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 58 x 45	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 61 x 45	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 60 x 45
Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindles Mower Deck Lift Features Cruise Control Headlights Hour Meter Cup Holder Fuel Level Indicator Maintenance Monitor Dimensions Length x Width x Height (inches)	28 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No Optional No Yes No No No	33 HI VAC® 1 1.5 - 4 6 Manual Lever Frame Hung 13-Gauge Steel Mechanical No 1-Bulb LED No Yes No No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No	46 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 14-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No	Side Discharge 2 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No 71 x 61 x 45	48 Side Discharge 3 1.5 - 4 7 Electric Frame Hung 12-Gauge Aluminum Mechanical Yes 2-Bulb Incandescent No Yes Yes No

Zero Turn Specifications

				1							
Model	360Z - 22/46	360Z - 23/42	360Z - 23/48	360Z - 21.5/48	360Z - 25/52	400Z - 21.5/48	400Z - 25/48	550Z - 24/52	550Z - 25/52	550Z - 24/61	550Z - 25/61
Engine											
Brand	Briggs & Stratton Intek™ V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV	Kawasaki® FR651V V-Twin OHV	Briggs & Stratton Professional Series™ V-Twin OHV	Kawasaki [®] FR651V V-Twin OHV	Briggs & Stratton® Commercial Series V-Twin OHV	Kawasaki® FR730V V-Twin OHV	Briggs & Stratton® Commercial Series V-Twin OHV	Kawasaki® FR730V V-Twin OHV	Briggs & Stratton® Commercial Series V-Twin OHV
Gross Horsepower / Cylinders	22*/2	23* / 2	23* / 2	21.5** / 2	25* / 2	21.5** / 2	25 [*] / 2	24** / 2	25* / 2	24** / 2	25* / 2
Engine Displacement (cc)	724	724	724	726	724	726	724	726	724	726	724
Choke / Throttle	Choke-a-Matic	ReadyStart®	ReadyStart®	Separate Controls	ReadyStart®	Separate Controls	Separate Controls	Separate Controls	Separate Controls	Separate Controls	Separate Controls
Start Type	Key	Кеу	Key	Key	Key	Key	Key	Key	Key	Key	Key
Engine Features	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter	Spin-On Oil Filter
Fuel Tank Capacity (U.S. Gallons)	3.0	3.0	3.0	3.0	3.0	5.5	5.5	5.5	5.5	5.5	5.5
12V Battery (cca)	230	230	230	230	230	300	300	300	300	300	300
Transaxles											
Transaxle Make	Hydro-Gear® EZT®	Hydro-Gear® EZT®	Hydro-Gear® EZT®	Hydro-Gear® EZT®	Hydro-Gear® ZT-2800®	Hydro-Gear® ZT-2800®	Hydro-Gear® ZT-2800®	Hydro-Gear® ZT-3100®	Hydro-Gear® ZT-3100®	Hydro-Gear® ZT-3100®	Hydro-Gear® ZT-3100®
Differential	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro
Speed- Fwd / Rev. (mph)	0-6 / 0-3	0-7 / 0-4	0-7 / 0-4	0-7 / 0-4	0-8 / 0-4	0-8/0-4	0-8/0-4	0-8/0-4	0-8/0-4	0-8/0-4	0-8/0-4
Brake	Integrated	Integrated	Integrated	Integrated	Integrated	Internal	Internal	Internal	Internal	Internal	Internal
Chassis											
Frame	12-Gauge Welded	12-Gauge Welded	12-Gauge Welded	12-Gauge Welded	12-Gauge Welded	11-Gauge Welded	11-Gauge Welded	11-Gauge Welded	11-Gauge Welded	11-Gauge Welded	11-Gauge Welded
Front Axle	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed
Front Tires (inches)	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	13 x 5	13 x 5	13 x 5	13 x 5
Rear Tires (inches)	18 x 8.5	20 x 8	20 x 8	20 x 8	20 x 10	20 x 10	20 x 10	20 x 10	20 x 10	20 x 10	20 x 10
Number of Anti-Scalp Wheels	2 Front	1 Front, 1 Rear	2 Front	2 Front	2 Front	1 Front	1 Front	4 Front	4 Front	4 Front	4 Front
Seat	15" Mid-Back, Adjustable	15" Mid-Back, Adjustable	15" Mid-Back, Adjustable	15" Mid-Back, Adjustable	15" Mid-Back, Adjustable	18" High-back, Adjustable	18" High-back, Adjustable	18" High-back, Adjustable	18" High-back, Adjustable	18" High-back, Adjustable	18" High-back, Adjustable
Steering	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever	Twin-Lever
Mower Deck	IWIII-LEVEI	IWIII-EEVEI	IWIII-EEVEI	IWIII-LEVEI	IWIII-EEVEI	IWIII-LEVEI	IWIII-LEVEI	TWIII-LEVEI	TWIII-LEVEI	TWIII-EEVET	IWIII-LEVEI
Deck Type	Stamped Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel	5 1 ° 1 C1 1	1		1	Fabricated Ctral	Fabricated Steel
	Stamped Steet					Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel	
Cutting Width (inches)	46	42				Fabricated Steel 48	Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel	
Cutting Width (inches) Mower Configuration	46 Side Discharge	42 Side Discharge	48	48	52	48	48	52	52	61	61
Mower Configuration	Side Discharge	Side Discharge	48 Side Discharge	48 Side Discharge		48 Side Discharge					
Mower Configuration Number of Blades	Side Discharge	Side Discharge	48 Side Discharge 3	48 Side Discharge	52 Side Discharge 3	48 Side Discharge 3	48 Side Discharge	52 Side Discharge	52 Side Discharge	61 Side Discharge	61 Side Discharge
Mower Configuration Number of Blades Height-of-Cut Range (inches)	Side Discharge 3 1.5 - 4.5	Side Discharge 2 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5	52 Side Discharge 3 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5	52 Side Discharge 3 1.5 - 4.5	52 Side Discharge 3 1.5 - 4.5	61 Side Discharge 3 1.5 - 4.5	61 Side Discharge 3 1.5 - 4.5
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions	Side Discharge 3 1.5 - 4.5 13	Side Discharge 2 1.5 - 4.5 13	48 Side Discharge 3 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5 13	52 Side Discharge 3 1.5 - 4.5 13	48 Side Discharge 3 1.5 - 4.5	48 Side Discharge 3 1.5 - 4.5	52 Side Discharge 3 1.5 - 4.5	52 Side Discharge 3 1.5 - 4.5	61 Side Discharge 3 1.5 - 4.5	61 Side Discharge 3 1.5 - 4.5
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement	Side Discharge 3 1.5 - 4.5 13 Electric	Side Discharge 2 1.5 - 4.5 13 Electric	48 Side Discharge 3 1.5 - 4.5 13 Electric	48 Side Discharge 3 1.5 - 4.5 13 Electric	52 Side Discharge 3 1.5 - 4.5 13 Electric	48 Side Discharge 3 1.5 - 4.5 12 Electric	48 Side Discharge 3 1.5 - 4.5 12 Electric	52 Side Discharge 3 1.5 - 4.5 12 Electric	52 Side Discharge 3 1.5 - 4.5 12 Electric	61 Side Discharge 3 1.5 - 4.5 12 Electric	61 Side Discharge 3 1.5 - 4.5 12 Electric
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed*	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed [‡] ROPS Rear Bumper	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No No	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed¹ ROPS Rear Bumper Hour Meter	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS Rear Bumper Hour Meter Cup Holder	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed¹ ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed¹ ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Dimensions	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes Yes Optional Accessory	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Dimensions Length x Width x Height (inches)	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No	48 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Yes	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Dimensions	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes Yes Optional Accessory	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed* ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Dimensions Length x Width x Height (inches)	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory 72 x 59 x 41	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes Yes Optional Accessory	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory
Mower Configuration Number of Blades Height-of-Cut Range (inches) Height-of-Cut Positions Blade Engagement Deck Suspension Deck Thickness Spindle Mower Deck Lift Features Cargo Bed¹ ROPS Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Dimensions Length x Width x Height (inches) Limited Warranty¹	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 14-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 2 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Optional Accessory No Yes Optional Accessory Yes No Optional Accessory	Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	3 1.5 - 4.5 13 Electric Frame Hung 12-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes No Optional Accessory	52 Side Discharge 3 1.5 - 4.5 13 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated Yes No Yes Optional Accessory Yes Optional Accessory	48 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes Optional Accessory	Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No No Yes Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	52 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory 78 x 63 x 66	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory	61 Side Discharge 3 1.5 - 4.5 12 Electric Frame Hung 10-Gauge Aluminum Mechanical, Foot Operated No Yes Yes Yes Yes Yes Optional Accessory 78 x 63 x 66



Easy to Use. Easy to Own.



Get your digital edition now!

Scan the QR code to download a digital edition.

Data rates apply.

© 2016 BRIGGS & STRATTON POWER PRODUCTS GROUP LLC. ALL RIGHTS RESERVED

MILWAUKEE, WI 53201 USA

SNAPPER.COM **F Y** S⁺ ►









Be careful fueling your small gasoline engines in your mowers. Fuel with ethanol can cause damage to your engine including poor starting, rough running, rust, corrosion and in some cases failure. www.LookBeforeYouPump.com